SCHMIDT 1915 multifunction

·**Warranty time:** 12 months
·**Packing:** 6 units in 1 truck
·**Delivery time: 10-60** days after deposit
·**Minimum quantity:** 1 units
·**Standard configurations:**
450kg rated load, CE certificate, KUBOTA D902 , 3way hydraulic joystick, quick hitch, hydrostatic drive, standard bucket, 23x8,50-12 tire,
,ELECTRONIC CONTROL OPERATING SYSTEM

·**Optionional attachments:**

Attachment	Price	Attachment	Price
Grab Bucket	EUR 1065		
Pitchfork	EUR 1065		
Barrel clamp	EUR 1102	Snow blade	EUR 997
Pallet fork	EUR 549	Sweeper Hydraulick	EUR 2025
Grass fork	EUR 1065	4 in 1 bucket	EUR 1199
Mixer bucket	EUR 2249	Hydraulic forks	EUR 1575
Sweeper standard	EUR 1605	Auger	EUR 1530

Specifications of 1915 wheel loader

1.0 Engine Details
(1) Model: KUBOTA D902
(2) Engine type: In-line arrangement, water-cooled, three cylinders diesel Engine
(3) Rated Power: 16,1KW
(4) Rated Speed: 1600 r/min (rpm)
(5) Fuel Consumption ratio in standard working condition: 260g/kw.H

2.0 Transmission System
(1) SM OLEODYNAMICA

3.0 Bucket
(1) Bucket Capacity: 0,2 m^3
(2) Bucket width: 930mm
(3) Bucket type: Heavy-duty
(4) Rated Load: 450kg
(5) Operating Weight: 1150kg

4.0 Overall Dimensions
(1) Overall Length (Bucket on ground position): 3200 mm
(2) Overall Height: 1945 mm
(3) Overall width: 930 mm
(4) Dumping Height: 2100 mm
(5) Lifting Height ; 2600 mm

5.0 Operating Specifications
(1) Steering System: Articulated Frame with hydraulic power steering
(2) Driving System: Hydostatic Drive

6.0 Brake System
(1) Parking Brake: hand brake

7.0 Tyre: 23x8.50-12

8.0 Wheelbase: 1200mm

60
80
100
C
H
°C
1/8
1/2
E
F
6.6

SCHMIDT
1915
SCHMIDT

SCHMIDT

SCHMIDT

SCHMIDT
1015
SCHMIDT

SCHMIDT

SCHMIDT
SCHMIDT
1915